

TorrentExam

Input your exam code ...

The passing rate of our valid exam braindumps for most certifications is high up to 99%. A small PDF dumps free is ready to download for new customers to tell if our exam dumps are suitable for their real exam.

All Products | Contact now

Why Choose Us



QUALITY AND VALUE

RealExamFree Practice Exams are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development - no all dumps.



TESTED AND APPROVED

We are committed to the process of vendor and third party approvals. We believe professionals and executives alike deserve the confidence of quality coverage these authorizations provide.



EASY TO PASS

If you prepare for the exams using our RealExamFree testing engine, It is easy to succeed for all certifications in the first attempt. You don't have to deal with all dumps or any free torrent / rapidshare all stuff.



TRY BEFORE BUY

RealExamFree offers free demo of each product. You can check out the interface, question quality and usability of our practice exams before you decide to buy.

Customer Reviews



I wasted a lot of money and failed twice. Thanks to HPE0-J78 exam collection I pass now.

Noel



realexamfree is a reliable company. I pass exam at first shot. Many thanks

Julie



Pass BIMF.EN successfully. Really good dumps. It saves me a lot of time. Wonderful!

Ahern



online test engine is very useful for me, because i could practice the C-TERP10-67 question dumps in my phone when i was waiting or on the bus even without internet, i could make the most of my time. Last week, i passed the C-TERP10-67. so i want to share the realexamfree with you guys. hope you will get a good result in test.

Carl

<http://www.torrentexam.com>

Best Exam Bootcamp & Excellent VCE Torrent & Satisfying Dumps Torrent

Exam : 70-552-Cplusplus

Title : UPGRADE:MCAD Skills to MCPD
Wdws Dvlpr by Using MS .NET
Fmwk

Vendors : Microsoft

Version : DEMO

1.You are developing a utility screen for a new client application. The utility screen displays a thermometer that conveys the current status of processes being carried out by the application. You need to draw a rectangle on the screen to serve as the background of the thermometer as shown in the exhibit. The rectangle must be filled with gradient shading. (Click the Exhibit button.) Which code segment should you choose?



- A. `Rectangle^ rectangle = gnew Rectangle(10, 10, 450, 25); LinearGradientBrush^ rectangleBrush = gnew LinearGradientBrush(rectangle, Color::AliceBlue, Color::CornflowerBlue, LinearGradientMode::ForwardDiagonal); Pen^ rectanglePen = gnew Pen(rectangleBrush); Graphics^ g = this->CreateGraphics(); g->DrawRectangle(rectanglePen, rectangle);`
- B. `Rectangle^ rectangle = gnew Rectangle(10, 10, 450, 25); LinearGradientBrush^ rectangleBrush = gnew LinearGradientBrush(rectangle, Color::AliceBlue, Color::CornflowerBlue, LinearGradientMode::ForwardDiagonal); Pen^ rectanglePen = gnew Pen(rectangleBrush); Graphics^ g = this->CreateGraphics(); g->FillRectangle(rectangleBrush, rectangle);`
- C. `RectangleF^ rectangle = gnew RectangleF(10f, 10f, 450f, 25f); array^ points = gnew array^ {gnew Point(0, 0), gnew Point(110, 145)}; LinearGradientBrush^ rectangleBrush = gnew LinearGradientBrush(rectangle, Color::AliceBlue, Color::CornflowerBlue, LinearGradientMode::ForwardDiagonal); Pen^ rectanglePen = gnew Pen(rectangleBrush); Graphics^ g = this->CreateGraphics(); g->DrawPolygon(rectanglePen, points);`
- D. `RectangleF^ rectangle = gnew RectangleF(10f, 10f, 450f, 25f); SolidBrush^ rectangleBrush = gnew SolidBrush(Color::AliceBlue); Pen^ rectanglePen = gnew Pen(rectangleBrush); Graphics^ g = this->CreateGraphics(); g->DrawRectangle(rectangleBrush, rectangle);`

Answer:B

2.You create an application to send a message by e-mail. An SMTP server is available on the local subnet. The SMTP server is named smtp.contoso.com. To test the application, you use a source address, me@contoso.com, and a target address, you@contoso.com. You need to transmit the e-mail message. Which code segment should you use?

- A. `MailAddress addrFrom("me@contoso.com", "Me");MailAddress addrTo("you@contoso.com", "You");MailMessage message(%addrFrom, %addrTo);message.Subject = "Greetings!";message.Body = "Test";message.Dispose();`
- B. `String^ strSmtpClient = "smtp.contoso.com";String^ strFrom = "me@contoso.com";String^ strTo = "you@contoso.com";String^ strSubject = "Greetings!";String^ strBody = "Test";MailMessage msg(strFrom, strTo, strSubject, strSmtpClient);`
- C. `MailAddress addrFrom("me@contoso.com");MailAddress addrTo("you@contoso.com");MailMessage message(%addrFrom, %addrTo);message.Subject = "Greetings!";message.Body = "Test";SmtpClient client("smtp.contoso.com");client.Send(%message);`
- D. `MailAddress^ addrFrom = gnew MailAddress("me@contoso.com", "Me");MailAddress^ addrTo = gnew MailAddress("you@contoso.com", "You");MailMessage^ message = gnew MailMessage(addrFrom, addrTo);message->Subject = "Greetings!";message->Body = "Test";SocketInformation info;Socket^ client = gnew Socket(info);System::Text::ASCIIEncoding^ enc =`

```
gcnew          System::Text::ASCIIEncoding();array^          msgBytes          =
enc->GetBytes(message->ToString());client->Send(msgBytes);
```

Answer:C

3.You need to write a code segment that will add a string named strConn to the connection string section of the application configuration file. Which code segment should you use?

```
A.System::Configuration::Configuration^          myConfig          =
ConfigurationManager::OpenExeConfiguration( ConfigurationUserLevel::None);myConfig->ConnectionSt
rings->ConnectionStrings->Add(          gcnew          ConnectionStringSettings("ConnStr1",
strConn));myConfig->Save();
```

```
B.System::Configuration::Configuration^          myConfig          =
ConfigurationManager::OpenExeConfiguration( ConfigurationUserLevel::None);myConfig->ConnectionSt
rings->ConnectionStrings->Add(          gcnew          ConnectionStringSettings("ConnStr1",
strConn));ConfigurationManager::RefreshSection("ConnectionStrings");
```

```
C.ConfigurationManager::ConnectionStrings::Add(          gcnew          ConnectionStringSettings("ConnStr1",
strConn));ConfigurationManager::RefreshSection("ConnectionStrings");
```

```
D.ConfigurationManager::ConnectionStrings::Add(          gcnew          ConnectionStringSettings("ConnStr1",
strConn));System::Configuration::Configuration^          myConfig          =
ConfigurationManager::OpenExeConfiguration( ConfigurationUserLevel::None);myConfig->Save();
```

Answer:A

4.You are using the Microsoft Visual Studio 2005 IDE to examine the output of a method that returns a string. You assign the output of the method to a string variable named fName. You need to write a code segment that prints the following on a single line The message: "Test Failed: " The value of fName if the value of fName does not equal "John" You also need to ensure that the code segment simultaneously facilitates uninterrupted execution of the application. Which code segment should you use?

```
A.Debug::Assert(fName == "John", "Test Failed: ", fName);
```

```
B.Debug::WriteLineIf(fName != "John", fName, "Test Failed");
```

```
C.if (fName != "John") { Debug::Print("Test Failed: "); Debug::Print(fName);}
```

```
D.if (fName != "John") { Debug::WriteLine("Test Failed: "); Debug::WriteLine(fName);}
```

Answer:B

5.You are developing an application that will deploy by using ClickOnce. You need to test if the application executes properly. You need to write a method that returns the object, which prompts the user to install a ClickOnce application. Which code segment should you use?

```
A.return ApplicationSecurityManager::ApplicationTrustManager;
```

```
B.return AppDomain::CurrentDomain::ApplicationTrust;
```

```
C.return gcnew HostSecurityManager();
```

```
D.return SecurityManager::PolicyHierarchy();
```

Answer:A

6.You are developing a method to hash data with the Secure Hash Algorithm. The data is passed to your method as a byte array named message. You need to compute the hash of the incoming parameter by using SHA1. You also need to place the result into a byte array named hash. Which code segment should you use?

```
A.SHA1          ^sha          =          gcnew          SHA1CryptoServiceProvider();array^hash          =
nullptr;sha->TransformBlock(message, 0, message->Length, hash, 0);
```

```
B.SHA1          ^sha          =          gcnew          SHA1CryptoServiceProvider();array^hash          =
```

```
BitConverter::GetBytes(sha->GetHashCode());
```

```
C.SHA1 ^sha = gcnew SHA1CryptoServiceProvider();array^hash = sha->ComputeHash(message);
```

```
D.SHA1 ^sha = gcnew SHA1CryptoServiceProvider();sha->GetHashCode();array^hash = sha->Hash;
```

Answer:C

7.You create a DirectorySecurity object for the working directory. You need to identify the user accounts and groups that have read and write permissions. Which method should you use on the DirectorySecurity object?

A.the GetAuditRules method

B.the GetAccessRules method

C.the AccessRuleFactory method

D.the AuditRuleFactory method

Answer:B

8.You are creating an assembly named Assembly1. Assembly1 contains a public method. The global cache contains a second assembly named Assembly2. You must ensure that the public method is only called from Assembly2. Which permission class should you use?

A.GacIdentityPermission

B.PublisherIdentityPermission

C.DataProtectionPermission

D.StrongNameIdentityPermission

Answer:D

9.You are changing the security settings of a file named MyData.xml. You need to preserve the existing inherited access rules. You also need to prevent the access rules from inheriting changes in the future. Which code segment should you use?

```
A.FileSecurity^ security = gcnew FileSecurity("mydata.xml",AccessControlSections::All);security->SetAccessRuleProtection(true, true);File::SetAccessControl("mydata.xml", security);
```

```
B.FileSecurity^ security = gcnew FileSecurity();security->SetAccessRuleProtection(true, true);File::SetAccessControl("mydata.xml", security);
```

```
C.FileSecurity^ security = File::GetAccessControl("mydata.xml");security->SetAccessRuleProtection(true, true);
```

```
D.FileSecurity^ security = File::GetAccessControl("mydata.xml");security->SetAuditRuleProtection(true, true);File::SetAccessControl("mydata.xml", security);
```

Answer:A

10.You are writing code for user authentication and authorization. The username, password, and roles are stored in your application data store. You need to establish a user security context that will be used for authorization checks such as IsInRole. You write the following code segment to authorize the user. if (!TestPassword(userName, password)) throw new Exception("could not authenticate user"); String[] userRolesArray = LookupUserRoles(userName); You need to complete this code so that it establishes the user security context. Which code segment should you use?

```
A.GenericIdentity ident = new GenericIdentity(userName);GenericPrincipal currentUser = new GenericPrincipal(ident, userRolesArray);Thread.CurrentPrincipal = currentUser;
```

```
B.WindowsIdentity ident = new WindowsIdentity(userName);WindowsPrincipal currentUser = new WindowsPrincipal(ident);Thread.CurrentPrincipal = currentUser;
```

```
C.NTAccount userNTName = new NTAccount(userName);GenericIdentity ident = new
```

```
GenericIdentity(userNTName.Value);GenericPrincipal currentUser= new GenericPrincipal(ident,
userRolesArray);Thread.CurrentPrincipal = currentUser;
D.IntPtr token = IntPtr.Zero;token = LogonUserUsingInterop(userName,
encryptedPassword);WindowsImpersonationContext ctx = WindowsIdentity.Impersonate(token);
```

Answer:A

11.You are developing a server application that will transmit sensitive information on a network. You create an X509Certificate object named certificate and a TcpClient object named client. You need to create an SslStream to communicate by using the Transport Layer Security 1.0 protocol. Which code segment should you use?

A.SslStream ^ ssl = gcnew SslStream(Client->GetStream());ssl->AuthenticateAsServer(certificate, false, SslProtocols::None, true);

B.SslStream ^ssl = gcnew SslStream(Client->GetStream());ssl->AuthenticateAsServer(certificate, false, SslProtocols::Ssl3, true);

C.SslStream ^ssl = gcnew SslStream(Client->GetStream());ssl->AuthenticateAsServer(certificate, false, SslProtocols::Ssl2, true);

D.SslStream ^ssl = gcnew SslStream(Client->GetStream());ssl->AuthenticateAsServer(certificate, false, SslProtocols::Tls, true);

Answer:D

12.You are developing an auditing application to display the trusted ClickOnce applications that are installed on a computer. You need the auditing application to display the origin of each trusted application. Which code segment should you use?

A.ApplicationTrustCollection^ trusts;trusts= ApplicationSecurityManager::UserApplicationTrusts;for(int i=0;iCount;i++){ApplicationTrust^ trust = trusts[i];System::Console::WriteLine(trust->ToString());}

B.ApplicationTrustCollection^ trusts;trusts = ApplicationSecurityManager::UserApplicationTrusts;for(int i=0;iCount;i++){ApplicationTrust^ trust = trusts[i];System::Console::WriteLine(trust->ExtraInfo->ToString());}

C.ApplicationTrustCollection^ trusts;trusts = ApplicationSecurityManager::UserApplicationTrusts;for(int i=0;iCount;i++){ApplicationTrust^ trust = trusts[i];System::Console::WriteLine(trust->ApplicationIdentity->FullName);}

D.ApplicationTrustCollection^ trusts;trusts = ApplicationSecurityManager::UserApplicationTrusts;for(int i=0;iCount;i++){Object^ trust = trusts[i];System::Console::WriteLine(trust->ToString());}

Answer:C

13.You are developing a method to call a COM component. You need to use declarative security to explicitly request the runtime to perform a full stack walk. You must ensure that all callers have the required level of trust for COM interop before the callers execute your method. Which attribute should you place on the method?

A.[SecurityPermission(SecurityAction::Demand, Flags=SecurityPermissionFlag::UnmanagedCode)]

B.[SecurityPermission(SecurityAction::LinkDemand, Flags=SecurityPermissionFlag::UnmanagedCode)]

C.[SecurityPermission(SecurityAction::Assert, Flags = SecurityPermissionFlag::UnmanagedCode)]

D.[SecurityPermission(SecurityAction::Deny, Flags = SecurityPermissionFlag::UnmanagedCode)]

Answer:A

14.You are developing a method to hash data for later verification by using the MD5 algorithm. The data is passed to your method as a byte array named message. You need to compute the hash of the incoming parameter by using MD5. You also need to place the result into a byte array. Which code segment should

you use?

- A. `HashAlgorithm ^algo = HashAlgorithm::Create("MD5"); hash = algo->ComputeHash(message);`
- B. `HashAlgorithm ^algo = HashAlgorithm::Create("MD5"); hash = BitConverter::GetBytes(algo->GetHashCode());`
- C. `HashAlgorithm ^algo; algo = HashAlgorithm::Create(message->ToString()); hash = algo->Hash;`
- D. `HashAlgorithm ^algo = HashAlgorithm::Create("MD5"); hash = nullptr; algo->TransformBlock(message, 0, message->Length, hash, 0);`

Answer:A

15. You are developing an application that will use custom authentication and role-based security. You need to write a code segment to make the runtime assign an unauthenticated principal object to each running thread. Which code segment should you use?

- A. `AppDomain^ domain = AppDomain::CurrentDomain; domain->SetPrincipalPolicy(PrincipalPolicy::WindowsPrincipal);`
- B. `AppDomain^ domain = AppDomain::CurrentDomain; domain->SetThreadPrincipal(gcnew WindowsPrincipal(nullptr));`
- C. `AppDomain^ domain = AppDomain::CurrentDomain; domain->SetAppDomainPolicy(PolicyLevel::CreateAppDomainLevel());`
- D. `AppDomain^ domain = AppDomain::CurrentDomain; domain->SetPrincipalPolicy(PrincipalPolicy::UnauthenticatedPrincipal);`

Answer:D

16. You are developing an application that runs by using the credentials of the end user. Only users who are members of the Administrator group get permission to run the application. You write the following security code to protect sensitive data within the application. `bool isAdmin = false; WindowsBuiltInRole role = WindowsBuiltInRole.Administrator; ... if (!isAdmin) throw new Exception("User not permitted");` You need to add a code segment to this security code to ensure that the application throws an exception if a user is not a member of the Administrator group. Which code segment should you use?

- A. `WindowsPrincipal currentUser = (WindowsPrincipal)Thread.CurrentPrincipal; isAdmin = currentUser.IsInRole(role);`
- B. `WindowsIdentity currentUser = WindowsIdentity.GetCurrent(); foreach (IdentityReference grp in currentUser.Groups) { NTAccount grpAccount = ((NTAccount)grp.Translate(typeof(NTAccount))); isAdmin = grp.Value.Equals(role); if (isAdmin) break; }`
- C. `GenericPrincipal currentUser = (GenericPrincipal)Thread.CurrentPrincipal; isAdmin = currentUser.IsInRole(role.ToString());`
- D. `WindowsIdentity currentUser = (WindowsIdentity)Thread.CurrentPrincipal.Identity; isAdmin = currentUser.Name.EndsWith("Administrator");`

Answer:A

17. You need to create a method to clear a Queue named q. Which code segment should you use?

- A. `for each (Object^ e in q) { q.Dequeue(); }`
- B. `for each (Object^ e in q) { q.Enqueue(0); }`
- C. `q.Clear();`
- D. `q.Dequeue();`

Answer:C

18. You are creating a class that uses unmanaged resources. This class maintains references to managed resources on other objects. You need to ensure that users of this class can explicitly release resources

when the class instance ceases to be needed. Which three actions should you perform? (Each correct answer presents part of the solution. Choose three.)

- A. Define the class such that it inherits from the WeakReference class.
- B. Define the class such that it implements the IDisposable interface.
- C. Create a class destructor that calls methods on other objects to release the managed resources.
- D. Create a class destructor that releases the unmanaged resources.
- E. Create a Dispose method that calls System.GC.Collect to force garbage collection.
- F. Create a Dispose method that releases unmanaged resources and calls methods on other objects to release the managed resources.

Answer: B D F

19. You are writing a custom dictionary. The custom-dictionary class is named MyDictionary. You need to ensure that the dictionary is type safe. Which code segment should you use?

- A. `public ref class MyDictionary : public Dictionary{}`;
- B. `public ref class MyDictionary : public Hashtable{}`;
- C. `public ref class MyDictionary : public IDictionary{}`;
- D. `public ref class MyDictionary{}; Dictionary t = gcnew Dictionary(); MyDictionary dictionary = (MyDictionary)t;`

Answer: A

20. You are creating an undo buffer that stores data modifications. You need to ensure that the undo functionality undoes the most recent data modifications first. You also need to ensure that the undo buffer permits the storage of strings only. Which code segment should you use?

- A. `Stack undoBuffer = gcnew Stack();`
- B. `Stack undoBuffer = gcnew Stack();`
- C. `Queue undoBuffer = gcnew Queue();`
- D. `Queue undoBuffer = gcnew Queue();`

Answer: A